

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (previously presented): A method of sending messages in a wireless communication network, comprising:

transmitting from a subscriber's mobile station to a control center a predefined message initiation code initiating a messaging session, a message identifier identifying a predefined, personalized message and an identifier of a receiving station, wherein the predefined, personalized message is designed by or on behalf of the subscriber.

2. (previously presented): The method according to claim 1, further comprising:  
receiving a message delivery notification at the mobile station indicating transmission of the personalized message to the receiving station.

3. (previously presented): The method according to claim 1, further comprising:  
retrieving the predefined message corresponding to the message identifier; and  
transmitting the retrieved predefined message to the receiving station.

4. (previously presented): The method according to claim 1, wherein the identifier of the receiving station is a telephone number.

5. (previously presented): The method according to claim 1, wherein the identifier of the receiving station is a distribution list identifier.

6. (currently amended): The method according to claim 1, wherein the wireless communication network is not enabled for ~~message~~mobile originated ~~origination~~ (MO) messaging.

7. (original): The method according to claim 1, wherein the mobile station is a wireless application protocol (WAP) enabled mobile station.

8. (original): The method of claim 1, wherein the wireless communication network is one of a Wideband Code Division Multiple Access (Wideband CDMA) network, a CDMA2000 network, a Time Division Multiple Access (TDMA) network, a General Packet Radio Service (GPRS) network, a IS-41 network, a IS-138 network, and a IS-54 network.

9. (currently amended): A method for ~~sending~~receiving messages in a wireless communication network, comprising:

receiving from a subscriber's mobile station a signal containing a predefined message initiation code initiating a wireless messaging session, and a message identifier identifying a predefined, personalized message, wherein the predefined, personalized message is defined by or on behalf of the subscriber; and

retrieving the predefined, personalized message identified by the message identifier.

10. (original): The method according to claim 9, wherein the signal received from the subscriber's mobile station includes an identifier of a receiving station; the method further comprising transmitting the retrieved predefined message to the receiving station.

11. (original): The method according to claim 9, further comprising:  
prior to receiving said signal, receiving the predefined message in a message definition mode;

storing in a database the predefined message in association with an identifier of the subscriber and the message identifier.

12. (original): The method according to claim 10, further comprising:

sending a message transmission notification to the subscriber's mobile station when the predefined message is transmitted to the receiving station.

13. (original): The method of claim 9, wherein the wireless communication network is one of a Wideband Code Division Multiple Access (Wideband CDMA) network, a CDMA2000 network, a Time Division Multiple Access (TDMA) network, a General Packet Radio Service (GPRS) network, a IS-41 network, a IS-138 network, and a IS-54 network.

14. (previously presented): A system for wireless initiated messaging, comprising:  
a personalized message database storing therein messages predefined by or on behalf of a subscriber and in association with the subscriber and a message identifier; and  
a call control center coupled to the personalized message database,  
wherein in response to receiving a signal comprising a predefined message initiation code to trigger sending a request to said database, a message identifier identifying one of the predefined messages, and an identifier of a receiving station, the call control center retrieves the predefined message from the personalized message database based on said message identifier and identifier of said receiving station and sends the retrieved predefined message to the receiving station.

15. (original): The system according to claim 14, wherein the call control center transmits a message delivery notification to the mobile station that sent the signal, when the predefined message is sent to the receiving mobile station.

16. (currently amended): The system according to claim 14, wherein the call control center is part of a wireless communications network that does not support ~~message~~mobile ~~originated~~ (MO) messaging.

17. (original): The system according to claim 14, wherein the call control center in response to receiving from the mobile station a signal containing the predefined message initiation code and a message identifier identifying an index control message, retrieves from the personalized message database the messages predefined for the subscriber and corresponding message numbers, and transmits said messages and message numbers to the mobile station.

18. (original): The system of claim 14, wherein the system is a wireless communication network according to one of a Wideband Code Division Multiple Access (Wideband CDMA) network, a CDMA2000 network, a Time Division Multiple Access (TDMA) network, a General Packet Radio Service (GPRS) network, a IS-41 network, a IS-138 network, and a IS-54 network.

19. (original): A mobile communications device, comprising:

a display;

an input unit for inputting a message number; a microprocessor;

a memory having recorded therein a computer program,

wherein the computer program is executed by the microprocessor causing a predetermined short code and the message number to be transmitted; and if the message number input corresponds to a request for message information, the device receives the message information including messages predefined by or on behalf of a user and displays the received messages on the display as selectable messages.

20. (original): The mobile communications device according to claim 19, wherein in response to the user selecting one of the displayed messages the device transmits the predetermined short code, an indicator of the selected message and a receiving device identifier to initiate delivery of the selected message to the receiving device identified by the receiving device identifier.

21. (original): The mobile communications device according to claim 20, wherein the mobile communication device receives a message delivery notification indicating the selected message was delivered to the receiving device identified by the receiving device identifier.

22. (original): The mobile communications device according to claim 19, wherein the mobile communications device operates according to a wireless application protocol (WAP).

23. (currently amended): The mobile communications device according to claim 19, wherein the mobile communications device operates in a wireless communication network that does not support ~~message~~ mobile originated ~~origination~~ (MO) messaging.

24. (original): The mobile communications device according to claim 19, wherein the receiving device identifier is a telephone number.

25. (original): The mobile communications device according to claim 20, wherein the receiving device identifier identifies a distribution list.

26-33 (canceled).

34. (previously presented): A method of sending messages in a wireless communication network, comprising:

designing a personal, short communication message by a subscriber;

storing said message in a database;

transmitting from a subscriber's mobile station to a control center a message initiation code to initiate a query to said database, a message identifier identifying said personal message and an identifier of a receiving station;

transmitting a message identified by said message identifier to a receiver station.

35. (previously presented): The method of claim 34, wherein the wireless communication network is not enabled for mobile originated messaging.

36. (previously presented): The method of claim 35, wherein the wireless communication network does not support wireless application protocol (WAP).

37. (previously presented): The method of claim 34, wherein the wireless communication network supports mobile terminated messaging.

38. (previously presented): The method of claim 37, wherein the wireless communication network does not support wireless application protocol (WAP).

39. (previously presented): The method of claim 34, wherein said identifier of a receiving station is selected from an address book of said subscriber's mobile station.



40. (previously presented): The method of claim 39, wherein said identifier of a receiving station is a list with a plurality of receiver station identifiers.